

MIDIFORST dt hyd

150-350 bar | 190-400 l/min

SEPPI M.'s most classic forestry mulcher: the powerful MIDIFORST dt hyd

This mulcher has proven itself over the years. The frame and hood, built completely in wear-resistant steel, are equipped with counter knives that optimize mulching results.

The powerful rotor, with its forestry hammers and double drive, mulches bushes and wood of up to 30cm in diameter. It is also available with tungsten carbide tip hammers on request. There are different types of guard frames to choose from for felling operations and to protect the tractor.



Standard version and characteristics

- > Mulches wood up to 30 cm [12"] Ø
- > Working speed 0-5 km/h
- > Cat. 2 3-point linkage or universal attachment interface
- > Dual side belt transmission
- > Hydraulically operated hood
- > Chain protection
- > Chassis made of high tensile steel
- > Tempered counterknives
- > Supporting skids
- > Standard rotor with swinging forestry hammers

Optional configuration and accessories

- > Forestry rotor with fixed hammers MINI DUO OPT-228
- > Forestry rotor with swinging hammers OPT-193
- > Mechanical or hydraulic guard frame
- > Hydraulic block with pressure relief valve and internal hoses
- > Hydraulic motors with relief valve
- > M-BOOST™ automatic variable displacement motors
- > Toothed belt transmission
- > Interface plates for loaders

SPECIFICATIONS			
	200 cm [79"]	225 cm [89"]	250 cm [98"]
Working width	200 cm [79"]	225 cm [89"]	250 cm [98"]
Overall width	233 cm [92"]	258 cm [102"]	283 cm [111"]
Depth	128 cm [50"]	128 cm [50"]	128 cm [50"]
Height	115 cm [45"]	115 cm [45"]	115 cm [45"]
Weight (base value w/o options)	1.650 kg [3,640lb]	1.970 kg [4,340lb]	2.190 kg [3,830lb]
Belts	2 x 5	2 x 5	2 x 5
Swinging hammers standard	33	38	42
MINI DUO fixed hammers OPT-228	44	48	52
Swinging hammers OPT-193	33	38	42

- SWINGING FORESTRY HAMMER STANDARD
- FIXED HAMMER WITH 2 TIPS MADE OF TUNGSTEN CARBIDE OPT-228 · MINI DUO™
- SWINGING HAMMER WITH 3 TIPS MADE OF TUNGSTEN CARBIDE OPT-193

High-performance hydraulic drive

The powerful **MIDIFORST dt hyd** with double drive is compatible with tractors with hydraulic flow rates between 190 and 400 l/min and is available with different types of hydraulic motors. The most powerful and efficient, the M-BOOST™ motor, delivers 40% more torque than standard motors.

Your SEPPI M. dealer will help you choose the correct motor for your application.

M-BOOST

HYDRAULIC DRIVE	
Pressure	150-350 bar [2,175 - 5,075 psi]
Required hydraulic flow	190-400 l/min [50.2 - 105.7 gpm]
Required hydraulic hoses	3 (pressure, return, drainage)
Case drain pressure	max. 5 bar
REQUIRED HYDRAULIC FITTINGS	
Hydraulically operated hood	1 double acting
Hydraulic guard frame	1 double acting

